



US005690676A

United States Patent [19]

DiPoto et al.

[11] Patent Number: 5,690,676
[45] Date of Patent: Nov. 25, 1997

- [54] SUTURE ANCHOR AND DRIVE ASSEMBLY
- [75] Inventors: Gene Philip DiPoto, Cumberland, R.I.;
Jeffrey C. Cerier, Franklin, Mass.;
Russell F. Warren, Greenwich, Conn.;
Gerard S. Cariozzi, Weymouth; Paul
DiCarlo, E. Falmouth, both of Mass.;
James W. Dwyer, Brookfield, Conn.;
Alan Attridge Small, Needham, Mass.

4,776,328 10/1988 Frey et al. 128/92
4,895,148 1/1990 Bays et al. 606/213
4,968,315 11/1990 Gattuma 606/72
5,002,550 3/1991 Li 606/139
5,037,422 8/1991 Hayhurst et al. 606/72

FOREIGN PATENT DOCUMENTS

0260970 3/1988 European Pat. Off. .
2606270 5/1988 France .
WO89/01767 3/1989 WIPO .
WO89/10096 11/1989 WIPO .

- [73] Assignee: Smith & Nephew, Inc., Andover, Mass.

[21] Appl. No.: 509,966

[22] Filed: Aug. 1, 1995

Related U.S. Application Data

- [60] Continuation of Ser. No. 91,092, Jul. 12, 1993, abandoned, which is a division of Ser. No. 836,679, Feb. 14, 1992, Pat. No. 5,258,016, which is a continuation-in-part of Ser. No. 681,042, Apr. 5, 1991, abandoned, which is a continuation-in-part of Ser. No. 552,440, Jul. 13, 1990, Pat. No. 5,100,417.

- [51] Int. Cl.⁶ A61B 17/04
[52] U.S. Cl. 606/232; 606/72; 606/73
[58] Field of Search 606/65, 73, 86,
606/104, 139, 170, 220, 232

References Cited

U.S. PATENT DOCUMENTS

2,329,398 9/1943 Duffy 606/104
3,845,772 11/1974 Smith 606/104
4,409,974 10/1983 Freedland 128/92
4,454,875 6/1984 Pratt et al. .
4,496,468 1/1985 Li 606/232
4,532,926 8/1985 O'Holla 606/139
4,632,100 12/1986 Somers et al. 606/73
4,653,486 3/1987 Coker 128/92
4,669,473 6/1987 Richards et al. .
4,738,255 4/1988 Goble et al. 606/86

OTHER PUBLICATIONS

Arthrex Brochure—"Arthrex ESP System: Expanding Suture Plug"—Feb., 1991? [Published prior to Mar. 1, 1991].

Primary Examiner—Michael Buiz

Assistant Examiner—Daphna Shai

Attorney, Agent, or Firm—Fish & Richardson P.C.

[57]

ABSTRACT

A suture anchor and anchor driver device for securely and accurately positioning and installing the suture anchor in place. The anchor has a rounded or pointed head and one or more ridges around it to help force fit the anchor into a hole and to hold it in place. A suture is positioned through the anchor for subsequent use during the surgical procedure. The driver device has a handle and an elongated shaft and is used to position and install the anchor in place. The anchor preferably snap fits onto the end of the shaft. A depth guide can be integrally or removably positioned on the shaft to ensure correct depth of placement. Alternately, the driver shaft is hollow and the anchor is positioned inside it and is implanted with a pusher member. The ends of the suture are affixed to the driver handle. Grooves can be provided on the driver and the anchor to prevent the suture from interfering with the positioning and installation procedure.

18 Claims, 9 Drawing Sheets

